

1	RK	BATT [SW]	R	ON
2	LB	CHECK: BRAKE PRESSURE		3.000 PSI
3	LK	FIRE TEST [SW]	R	A (hold)
4	RK	SEAT ARM	L	ARM
5	RK	CANOPY [SW]	L	CLOSE
6	LK	FIRE TEST [SW]	L	B (hold)
7	LK	APU [SW]	R	ON
8	KB	Bodencrew.../Externe Elektrik.../An		#
9	LK	EXT PWR [SW]	R	RESET
10	LK	GND PWR 1, 2 and 4 [SW]	L	B ON (hold)
11	UFC	set ATC Frequency [RADIO]		
12	HTS	ATC/Request Engine Start		COMM SWITCH
13	LK	CHECK: APU READY		green LED
14	LK	ENG CRANK [SW]	R	R
15	LI	CHECK: ENGINE R RPM [IFEI]		>= 25 %
16	KB	Right Throttle: IDLE		RShift Pos 1
17	LI	set BINGO FUEL [IFEI]		~5.000 lbs
18	LI	MASTER CAUTION [BTN]	L	2xPRESS
19	RK	CONSOLE ⤴	W	BRT
20	RK	INST PNL ⤴	W	BRT
21	RK	FLOOD ⤴	W	BRT
22	RK	LT TEST [SW]	R	HOLD
23	LI	L-DDI ⤴	R	NIGHT/DAY
24	RI	R-DDI ⤴	R	NIGHT/DAY
25	MI	HUD BRT ⤴	W	BRT
26	MI	AMPCD BRT ⤴	W	BRT
27	MI	BLK LVL ⤴	W	
28	MI	ALT [SW]	R	RDR
29	RK	INS ⤴	R	GND CV
30	RK	RADAR ⤴	R	OPR
31	RK	BLEED AIR ⤴	R	NORM ⤴ NORM
32	LK	FCS RESET [BTN]	L	PRESS
33	LI	L-DDI SUPT/ FCS		OSB18/OSB15
34	RI	R-DDI [BIT FAILURES] STOP	L	OSB10
35	MI	CHECK: AMPCD		TIME: > 0:00
36	MI	AMPCD STD HDG	L	OSB19
37	LK	ENG CRANK [SW]	L	L
38	LI	CHECK: ENGINE L RPM [IFEI]		>= 25 %
39	KB	Left Throttle: IDLE		AltGr Pos 1
40	KB	Bodencrew.../Externe Elektrik.../Aus		#

41	LK	OBOGS [SW]	R	ON
42	LB	FLAPS [SW]	R	HALF
43	LB	HOOK BYPASS [SW]		FIELD CARRIER
44	LB	ANTI SKID [SW]		ON OFF
45	LB	LANDING/TAXI [SW]	R	ON
46	RI	R-DDI [BIT FAILURES] FCS-MC/GO	L	OSB05
47	RI+KB	R-DDI [FCS-MC]	L	OSB05+ Z
48	LK	STROBE [SW]	R	BRT
49	LK	POSITION ⤴	W	BRT
50	LK	FORMATION ⤴	W	BRT
51	RI	CHECK: R-DDI [FCS-MC]		FCSA+FCSB GO
52	MI	CHECK: AMPCD		QUAL: 0.5 OK
53	RK	ENG [SW]	R	ON
54	RK	FLIR [SW]	R	STBY
55	RK	INS ⤴	R	IFA
56	MI	CHECK: AMPCD OSB06		POS/AINS
57	RB	set RADAR ALTIMETER warning index ⤴	W	200 ft 80 ft
58	RI	uncage STANDBY ATTITUDE INDICATOR ⤴	W	ALIGN
59	LK	T/O TRIM [BTN]	L	PRESS
60	LI	L-DDI SUPT/ CHKLST		OSB18/OSB11
61	LI	CHECK: A/C WT		
62	HTS	adjust STAB TRIM as follows:		TRIM
		< 44.000 lbs		16°
		44.000 - 49.000 lbs		17°
		> 49.000		19°
63	KB	Bodencrew.../Radkeile.../Entfernen		#
64	LB	PARKING BRAKE [LEVER]	L	DISENGAGE
65	RB	CHECK: WING FOLD		SPREAD
66	KB	CHECK: align A/C at Catapult-Shuttle		F2
67	LB	LAUNCH BAR [SW]	L	EXTEND
68	KB	hook Launch Bar into Catapult Shuttle		U
69	LB	LAUNCH BAR [SW]	R	RETRACT
70	LI	L-DDI TAC/HUD		OSB18/OSB03
71	RI	R-DDI SUPT/ FCS		OSB18/OSB15
72	MI	> 3.000 ft: ALT [SW]	L	BARO
73	MI	RWR [ALR-67 POWER BTN]	L	ON
74	MI	ECM ⤴	R	STBY
75	MI	DISPENSER	R	ON
76	UFC	IFF [BTN]	L	ON
77	UFC	D/L [BTN]	L	ON